Stateline Power Corp **Call us at 1-800-524-8344**

60 Hertz Generator Set Models	SG-25	SG-30	SG-45	SG-60	SG-80	SG-100	SG-120
Standby Power, 1 Phase, KW / KVA	25 / 25	30 / 30	45 / 45	60 / 60	80 / 80	100 / 100	120 / 120
Prime Power, 1 Phase, KW / KVA	22 / 22	27 / 27	40 / 40	54 / 54	72 / 72	90 / 90	108 / 108
Stanby Power, 3 Phase, KW / KVA	25 / 31	30 / 37	45 / 56	60 / 75	80 / 100	100 / 125	125 / 150
Prime Power, 3 Phase, KW / KVA	22 / 27	27 / 33	40 / 50	54 / 67	72 / 90	90 / 112	108 / 135
Max. Amperes at 120/240 Volts, 1 Phase	104	125	187	250	333	416	500
Max. Amperes at 120/208 Volts, 3 Phase	86	104	156	208	278	347	415
Max. Amperes at 120/240 Volts, 3 Phase	75	90	135	180	240	300	360
Max. Amperes at 277/480 Volts, 3 Phase	37	45	66	90	120	150	180
General Motors Engine Model	GM 3.0L	GM 3.0L	GM 4.3L	GM 5.7L	GM 8.1L	GM 8.1L	Gm 8.1L/T
Aspiration	Natural	Natural	Natural	Natural	Natural	Natural	Turbo
Displacement (Liters)	3	3	4.3	5.7	8.1	8.1	8.1
Engine Power in HP at 1800 RPM	43	43	61	93	120	149	186
Frequency Regulation	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic
Battery Voltage	12 vdc	12 vdc	12 vdc	12 vdc	12 vdc	12 vdc	12 vdc
Fuel Consumption: **NG-1000 BTU/ cubic feet** **LP Vapor-2500 BTU / Cubic Feet**							
50% Load in Cubic Feet per Hour	169NG / 67LP	203NG / 80LP	344NG / 133LP	510NG / 204LP	771NG / 332LP	840NG / 390LP	1087NG / 429LP
75% Load in Cubic Feet per Hour	254NG / 101LP	305NG / 121LP	460NG / 186NG	639NG / 256LP	868NG / 408LP	910NG / 478LP	1234NG / 487LP
100% Load in Cubis Feet per Hour	304NG / 135LP	365NG / 162LP	550NG / 235LP	748NG / 299LP	1000NG / 459LP	1180NG / 602LP	1591NG / 628LP
Fuel Inlet Size in NPT	1"	1"	1"	1"	1.5"	1.5"	1.5"
Deluxe Enclosed Dimensions, Inches:							
Length	75	75	122	122	129	129	132
Width	32	32	36	36	40	40	44
Height	48	48	58	58	69	69	69
Dry Weight of Open Unit on Base in Lbs.	1280	1280	1870	2180	2380	2590	2780
Available in UL2200 Configuration	Yes	Yes	Yes	Yes	Yes	Yes	No